

Kawasaki Jet Ski Ultra 260LX

SPECIFICATIONS



Engine Type	Supercharged and inter-cooled, four-stroke, DOHC, four valve per cylinder, inline four-cylinder
Displacement	1,498 cc
Bore and Stroke	83 x 69.2 mm
Compression Ratio	8.4:1
Induction System	Roots-type supercharger with air-to-water intercooler
Maximum boost	11.4 psi
Maximum horsepower	260hp @ 7,750 rpm*
	*HP measured in PS at the crankshaft under controlled conditions. Actual performance may vary.
Cooling system	Inducted water
Fuel Injection	Digital Fuel Injection
Ignition	TCBI with Digital Advance
Starting	Electric
Lubrication	Semi-Dry Sump system
Coupling	Direct drive from engine
Propulsion system	155mm jet pump, axial-flow, single stage
Impeller	Three-blade, oval-edge stainless steel
Maximum Thrust	1,585 lb.
Overall Length	132.7 in.
Overall Width	47 in.
Overall Height	45.3 in.
Curb Weight**	1062.8 lb. ** Includes all necessary materials and fluids to operate correctly, full tank of fuel (more than 90% of capacity) and tool kit (if supplied)
Load Capacity	496 lbs
Storage Capacity	53 gal.
Fuel Capacity	20.6 gal.
Oil Capacity	5.3 qt.
Color	Jet White / Metallic Phantom Silver
Warranty	12 months
Good Times™ Protection Plan	12, 24, 36 or 48 months

*Note: Specifications and pricing are subject to change.

